

## Tripple Option Trading 211 cc

6 Heron Road, Rant-en-Dal, 1739  
 Tel: (082) 8541001 Fax: (086) 5167896  
 Trip.op.trading@gmail.com  
 VAT No. 4160223584  
 Reg No. 2002/053292/23



Our experienced consultants will assist you in choosing the proper flow meter for your application. And they will be pleased to offer installation guidance to assure that the flowmeter selected will perform as accurately as possible. Additionally, they will stand ready to support you with any after-sale assistance that you may require.

### Electric Fuel Flowmeter



#### Product Description

Diesel Fuel flowmeter is designed for non-commercial use only. It is used for diesel fuel, gasoline, kerosene. These flow meters are reliable, inexpensive, easy to install and simple to calibrate on the workplace. Not Suitable for Bleach, Hydrochloric Acid, Ink, Motor Oil and Salt Water

It has the advantage of large, easy to read numbers, quick reset knob, flexible flow-ports can be positioned vertically or horizontally. The easy reset register indicates product use up to 999. The master totalizer registers

Aluminum metering chamber, thread connection. Mechanical readout device with rotating wheels. Subtotals can be set to zero, total cannot be set to Zero.

Applicable medium	Diesel Fuel, Gasoline, Kerosene, etc
Measurement Scale	Litre
Working Temp	-20°C ~ 100°C
Installation mode	vertically
	horizontally
Max. Pressure	3.5Bar

Ideal working Pressure	0.05---0.1Mpa
Flow Rate:	1-60L/min
	8-80L/min
	20--120 L/min
	19--151 L/min
	Customized acceptable
Inlet & Outlet:	3/4"
	1"
	1.5"
	Customized acceptable
Precision:	Around $\pm 1\%$
	Around $\pm 2\%$
Shell material	Aluminum
	Plastic

**Tripple Option Trading 211 cc**

[Tel:+27- 82 854 1001](tel:+27-82-854-1001)

Email: [trip.op.trading@gmail.com](mailto:trip.op.trading@gmail.com)